

THR-Variant





STLZ 1550/.. - 3,81 - V - black - HT

**2-12 poles, Spacing 3,81 mm
insert required no. of poles ..**

How to order see page 11

Ratings:

		
Rated Voltage	300 V	160 V
Rated Current	8 A	9 A (T60)
Overvoltage Category		III
Rating Impulse Voltage/Dirt Level		2,5 kV/3

Dimensions

Spacing	3,81 mm
PCB Hole Diameter	1,2 mm


Materials

Insulating Material	LCP
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Contact Pin	Cu

Colour

black

STLZ 1550 VERTICAL



P = No. of poles

THR-Variant





STLZ 1550/.. - 3,81 - H - black - HT

**2-12 poles, Spacing 3,81 mm
insert required no. of poles ..**

How to order see page 11

Ratings:

		
Rated Voltage	300 V	160 V
Rated Current	8 A	9 A (T60)
Overvoltage Category		III
Rating Impulse Voltage/Dirt Level		2,5 kV/3

Dimensions

Spacing	3,81 mm
PCB Hole Diameter	1,2 mm


Materials

Insulating Material	LCP
Flammability Class	UL94 V-0
Temperature Range	-30°C/+105°C
Contact Pin	Cu

Colour

black

STLZ 1550 HORIZONTAL



P = No. of poles